

**Table 1.0 – CVET Series Flow Coefficients (150, 300, 600 ANSI Pressure Ratings)**

Valve Size (in)	L0	E0	L1*	E1*	L2*	E2*	L3*	E3*
	Linear Profile Full Capacity	Equal % Profile Full Capacity	Linear Profile #1 Noise Trim	Equal % Profile #1 Noise Trim	Linear Profile #2 Noise Trim	Equal % Profile #2 Noise Trim	Linear Profile #3 Noise Trim	Equal % Profile #3 Noise Trim
1	20.6	17.2	17.3	14.7	12	10.2	9.8	8.3
1-1/2	39.2	35.8	28	24	20	17	16	14
2	72.9	59.7	52	44	37	31	30	26
3	148	136	112	95	81	69	65	55
4	236	224	198	168	140	119	109	93
6	433	394	375	319	272	231	206	175
8	846	818	695	591	501	426	381	324

**Notes:**

1. E Series Trims provide Equal Percentage Flow Profile – Excellent for Flow Range-Ability
2. L Series Trims provide Linear Flow Profile – Excellent for Maximum Capacity
3. 0 = Indicates Full Capacity with No Noise Attenuation Trim
4. 1 = 1 - Stage Noise Attenuation Trim (Drilled Hole)
5. 2 = 2 - Stage Noise Attenuation Trim (Drilled Hole)
6. 3 = 3 - Stage Noise Attenuation Trim (Drilled Hole)

**Table 2.0 – CVET Series Valve Travel and Port Sizes (150, 300, 600 ANSI Pressure Ratings)**

Valve Size (in)	Valve Travel (in)	Control Valve Port Size			
		L0 / E0 (in)	L1 / E1 (in)	L2 / E2 (in)	L3 / E3 (in)
1	0.75	1-5/16	1-5/16	7/8	5/8
1 ½	0.75	1-7/8	1-7/8	1-5/16	1-5/16
2	1.125	2-5/16	2-5/16	1-7/8	1-5/16
3	1.5	3-7/16	3-7/16	2-5/16	1-7/8
4	2	4-3/8	4-3/8	3-7/16	2-7/8
6	2	7	7	5-3/8	5-3/8
8	3	8	8	7	6

**Notes:**

1. E Series Trims provide Equal Percentage Flow Profile – Excellent for Flow Range-Ability
2. L Series Trims provide Linear Flow Profile – Excellent for Maximum Capacity
3. 0 = Indicates Full Capacity with No Noise Attenuation Trim
4. 1 = 1 - Stage Noise Attenuation Trim (Drilled Hole)
5. 2 = 2 - Stage Noise Attenuation Trim (Drilled Hole)
6. 3 = 3 - Stage Noise Attenuation Trim (Drilled Hole)